

Fixed Height Barrier

HBF-01

- Prevents unauthorised access to staff or public car parks
- Restricts high sided vehicles or caravans
- Available in sizes 3m – 9m
- Varying heights options available 1.9m – 2.4m
- Surface Fixed or Root Fixed options
- Galvanised and or Powercoated options
- Highly effective deterrent
- Optional knocking bar and warning signage available



Height Restriction barrier is an effective method of preventing unauthorised access to any high sided vehicles such as truck and caravans. Manufactured from galvanised steel and painted finish to provide a durable and effective product. Optional extras available such as knocking bars, root fixed or surface fixed options.

Specification:

Materials: 80 x 80 x 5mm Steel Box Section

Surface Mounted Base Plate: 350 x 350 x 10mm with Gusset steel construction

Root Fixed: 600 mm dig in post with spigots for concreting into ground

Hot Dip Galvanised as standard

Painted Finish options



** This product is supplied as Galvanised. If Powdercoated and Galvanised option is selected, this will have an additional cost and will extend the lead time.

** Please note that this product is not suitable for marine environments unless Galvanised and Powercoated option is selected.

** Bespoke sizes are available and will be made to order. Please choose the next standard size up and specify on your order what exact size you require us to manufacture. Please note that if no bespoke size is selected, the height barrier will be made to the standard size selected.

Optional Extra's

Warning Signage, Knocking Bar, Manual Swing Gate,

Installation

Root Fixed - Recommended size for the concrete foundation is 700x700x700mm deep as a minimum for main posts. Catch post foundation should be a 300mm cube.

Surface Fixed - Main post requires 4 no 16mm bolts for the two upright posts. The base size is 400x400x10mm

Catch post requires 4 no 12mm bolts