

- Manual Swing Gate with lockable latch post
- Can be locked in the open and closed position
- Heavy Duty steel construction provides good security
- Available in sizes 3m 16m
- Warning Signage optional extra
- Surface Fixed or Root Fixed options
- Galvanised and or Powdercoated / Painted options



Manufactured in Britain, our strong and sturdy Manual Swing Gate is available in a variety of widths, from 3-6 meters. For larger spans, 2 gates can be used and locked centrally to create a span up to 12 meters wide. Gates are supplied with a lockable opening catch post for added safety (padlock not supplied). Height from ground to top of gate is 1100mm. Gates will be supplied hot dip galvanised and optional painted finish in a standard range of RAL colours is available.

Upright posts are available in surface mounted and root fixed options. (Surface Mounted option up to 5 meter width only recommended, for widths greater than 5 meters, Root Fixed option is advisable.)

## **SPECIFICATION**

Barrier Arm(s): 80 x 40 x 3mm rectangular hollow section Supporting Legs: heavy duty 200 x 200 x 6mm box section

Latch Post: 100 x 100 x 5mm Steel Box Section

Catch Post: 50 x 50 x 3mm Steel Box Section



- \*\* This product is supplied as Galvanised. If Powdercoated and Galvanised option is selected, this will have an additional cost and will extend the lead time. Please note that this product is not suitable for marine environments unless Galvanised and Powdercoated option is selected.
- \*\* Bespoke sizes are available and will be made to order. Please choose the next standard size up and specify on your order what exact size you require us to manufacture. Please note that if no bespoke size is selected, the height barrier will be made to the standard size selected.

Optional Extra's: Warning Signage, Lock Shroud

## Installation

Root fixed barriers have an additional 750mm of length on the legs for counter sunk options. For surface mounted options the base plates are fabricated from  $700 \times 700 \times 10$ mm steel plates with 18mm diameter bolt holes.